



LESA STRIP


For protection or repair, with **Lesastrip**, the results are long-lasting, smooth floor joints.

- NO MORE bumps and wobbles with lift trucks.
- NO MORE concrete chips and dust.
- NO MORE unsightly, unhygienic, even dangerous joints across your modern factory or warehouse, supermarket or shopping centre.

Lesastrip - there is no other effective protection for floor joints.

Lesastrip is an epoxy nosing system for repairing damaged floor joints which are unsightly, costly and often dangerous.

It is available in a range of sizes, and can be used to rebuild from mildly damaged to badly spalled joints.




**DON'T LET YOUR NEW FLOOR
DETERIORATE TO THIS**




PROTECT IT WITH LESASTRIP





Lesastrip has become an industry standard for permanent edge protection at shrinkage control joints and construction joints in concrete floor slabs. Lesa Systems 2017 Ltd has a range of products for use in the construction and protection of floor joints in industrial and retail buildings.

- **LESASTRIP™ RED** plus **LESASTRIP GREEN** for new floor construction
- **LESASTRIP™ S2 FOR HYGIENIC SEALANT** provision for floors in food or similar industries
- **SPECIAL TOPPING**s joint protection
- **REPAIR CAPABILITY** to damaged joints in existing floor slabs




Lesastrip™ Red SC20 (red tips)

Lesastrip™ Green CF30 (green tips)

Lesastrip™ Red and **Lesastrip™ Green** are for installation in new floor slabs.


The hard nosings to the concrete, formed on each edge of the joint by the **Lesacrete™** epoxy resin grout, provide permanent protection to concrete edges, preventing the deterioration at the floor joints which has troubled engineers and manufacturers and other building users for many years.

Use **Lesastrip™ Red** in sawn joints and **Lesastrip™ Green** in construction joints.





HYGIENIC FLOORS




Where health regulations require floors to be fully sealed to provide a continuous surface unable to harbor harmful organisms, a **Lesacrete™** joint can be provided with a rebate to take a flexible sealant.

By using a plastic pullout (**Lesastrip™ S2**) with **Lesastrip™ Green**, a slot is created in the floor into which a flexible sealant can be applied.

Because it acts only as a sealant, there is no need for the sealant to provide the conflicting characteristics of being firm enough to support the edge while being soft enough to be flexible; edge protection is provided by the **Lesacrete™** corbels.

SPECIAL TOPPING AND COATINGS




Lesacrete™ is available in white for terrazzo and similar toppings, as well as the standard grey for plain concrete floors.

White **Lesacrete** used with terrazzo in shopping centre and supermarkets creates a floor with joints which are durable but barely visible.

The Lesa system is excellent in joints under acrylic-based and epoxy resin coatings and toppings. The joint edge protection provided by **Lesastrip™** eliminates a major source of deterioration of these floor membranes.



REPAIRS



The Lesa System is ideal for repairing damaged joints in existing floors. A deeper saw cut than for new floor installation may be required, and **Lesastrip Green** is used.

In deep cuts the **Lesastrip E** can be used to increase the effective height of the strip (for low quality concrete.)

For extra wide damaged joints, the large **Lesastrip A** section (75 mm deep) can be used.

When completed, the repaired edges will provide a service capability better than the original joints.

While the Lesa System cannot overcome any shortcoming in the original concrete, the installation of **Lesa Joint Edge Protection** will generally restore fully the serviceability of the slab and extend its useful life for many years.

