

# PENTRA-FINISH (HG)



## Pentra-Finish™ (HG) Advanced High-gloss Stain and Wear Protection Finish

### PRODUCT DESCRIPTION

**Pentra-Finish™ (HG) is a patented, high-gloss, stain and wear resistant finish for improving the sheen, hardness and chemical resistance of natural and cast stone, terrazzo, masonry, and other cement-based surfaces.** This water-based, lithium fortified chemical polish dries quickly to a clear, extremely hard, micro-coating that tenaciously bonds and reacts with the substrate forming an insoluble bond. Formulated using reactive silicon hybrid polymer technology (Si RE)<sup>™</sup> for extreme gloss, rapid shine development and excellent wear properties, this novel treatment eliminates the need

for floor waxes, liquid polishes and conventional resin based coatings. Best results and coverage will be obtained by densifying the surface with approved Nano-Lithium® Densifier before applying **Pentra-Finish™ (HG)**.

Because of its unique chemistry, **Pentra-Finish™ (HG)** will not lift or peel from the surface. Periodic recoating requires no stripping as the material doesn't build up. **Pentra-Finish™ (HG)** is non-toxic, non-hazardous, and VOC compliant in all areas of the world with less than 50 grams per liter VOC content. The easy-to-use finish is tough, mark-resistant,

fast drying and non-streaking. The treatment is used in conjunction with a high-speed burnisher on non-porous stone, masonry and Portland cement based building materials to provide superior clarity and improved resistance against water and water-borne stains from accidental spills, oils, dirt and grime. Ideal for ground and polished concrete surfaces as well as integrally colored, dyed and/or stained concrete. **Pentra-Finish™ (HG)** enhances the color intensity of natural and cast stone and integrally colored, dyed, or acid stained decorative concrete.

### KEY BENEFITS

- Delivers rapid shine development with increased abrasion and stain resistance as well as superior gloss retention
- Keeps dirt and contaminants from penetrating, making cleaning faster, more effective and more economical
- Ready to use in a few hours--rapidly cures into a durable finish for facilities that require maximum protection and little-to-no downtime
- Forms a protective "micro surface layer" that is breathable, dense, abrasion resistant, and that will not peel or flake
- Reduces maintenance, cleaning costs and costly repairs--simply damp mop or machine scrub
- No build up--periodic re-application is simple and requires no stripping



700 Great South Road, Penrose  
P O Box 9826, Auckland, New Zealand  
[www.lesasystems.co.nz](http://www.lesasystems.co.nz)

Tel: 64 9 526 7136 Fax: 64 9 525 2139  
Freephone: 0800 74 LESA (0800 74 5372)  
Email: [sales@lesasystems.co.nz](mailto:sales@lesasystems.co.nz)

# PENTRA-FINISH (HG)



- Prolongs shine of polished concrete surfaces
- Safe for food contact per SGS Testing (21 CFR 175.300)

## USES

### Interior Flooring Non-Porous Ground, Honed, Polished Or Burnished Concrete Surfaces

**Commercial:** Grocery Stores, Office Building, Retail, Banks, Malls, Warehouses, Distribution Centers

**Industrial:** Food Processing Facilities, Cold Storage / Freezers, Beverage and Manufacturing Plants

**Institutional:** Churches, Hospitals, Universities, Schools, Museums Theme & Leisure: Resorts, Hotels, Casinos, Restaurants, Theaters  
**Governmental:** Federal & State Buildings, Prisons

**Residential:** Concrete floors and Garages

## APPLICATION

**BEFORE APPLICATION, ALWAYS DO A SMALL TEST SAMPLE IN A LESS-VISIBLE AREA TO BE SURE THERE ARE NO VARIABLES OR CONTAMINANTS IN THE SUBSTRATE THAT MAY BE INCOMPATIBLE WITH THIS PRODUCT.**

Surface Preparation: Be sure surface to be treated is clean and dry. **Pentra-Finish™ (HG)** will not hide stains. Aggressive scrubbing with a neutral to alkali cleaner is recommended. Avoid citrus or butyl compounds when cleaning. **Finish™ (HG)** will not bond to acidic surfaces so if applying over an acid stain, neutralize thoroughly first.

**Mixing:** Lightly stir before each use. Do not over mix or bubbles and/or foaming can occur and make uniform application more difficult.

**Placement:** IMPORTANT Do not over apply. Very thin coats are best. Apply **Finish™ (HG)** using a micro fiber pad that has been pre-dampened with water. Using a pump up sprayer or HVLP sprayer, spray lightly over the top of the area to be treated, and then spread material thinly and evenly using the micro fiber pad over the rest of the area. For best results, limit the size of the area being treated at any one time to a 6.1 m x 6.1 m section. Spread at a rate of 37-74 sq. m/L depending on porosity of the surface. Spray another line of material when the applicator pad begins to drag. Do not work material into the surface-spread it and leave it. Allow each application to dry at least 30-60 minutes between coats or before using.

Second applications will improve sheen and stain protection. Buffing with a high-speed burnisher (1500-2100 rpm) and a hog's hair pad between coats is recommended and will speed curing and improve sheen. Second coats will usually take no more than 74 - 98 sq. m/L followed by a burnish. Do not cover treated surfaces for at least 1 week as protective coverings may slow curing and cause some whitening by trapping moisture.

## ESTIMATED COVERAGE

1st Coat:	37 - 74 sq. m/L
2nd and subsequent coats:	74 - 98 sq. m/L

Texture and absorption of surface will determine final coverage rates. Porous concrete surfaces may require additional material.

## CLEAN UP

Wash equipment with soap and water. Although **Pentra-Finish™ (HG)** is non-toxic and environmentally friendly, it is alkaline. Use the material completely, or dry it out and dispose of it properly per local regulations. Do not pour down sanitary sewers or into storm drains.



700 Great South Road, Penrose  
P O Box 9826, Auckland, New Zealand  
[www.lesasystems.co.nz](http://www.lesasystems.co.nz)

Tel: 64 9 526 7136 Fax: 64 9 525 2139  
Freephone: 0800 74 LESA (0800 74 5372)  
Email: [sales@lesasystems.co.nz](mailto:sales@lesasystems.co.nz)

# PENTRA-FINISH (HG)



## MAINTENANCE

Routine sweeping, mopping, washing and mechanical scrubbing of floors with water and neutral pH cleaners (if necessary) is recommended. Plain water only is sufficient for most environments. DO NOT USE cleaners that are acidic or that have citrus (d-Limonene) or Butyl compounds. Although **Pentra-Finish™ (HG)** is chemically resistant and helps reduce staining, some compounds, especially acids, may damage the surface, and therefore it may not be suitable for some applications. If unsure, check with a Convergent technical representative. Regular maintenance and cleaning will help prolong surface shine. Wipe up any chemical spills as soon as possible.

## SAFETY/HEALTH INFORMATION

**KEEP OUT OF REACH OF CHILDREN.** Dispose of waste material in accordance with federal, state and local requirements. Although the material is non-toxic and nonhazardous, the treatment is alkaline and may cause eye and skin irritation. Wear eye protection and gloves. If splashed in eyes, rinse with water and consult a doctor if irritation persists. Wash promptly from skin. Do not take internally-if swallowed, do not induce vomiting-drink water and call a physician. Avoid contact with eyes. Protective clothing is recommended. Surfaces may be slippery when wet with product. Additional precautions, safety information and first aid treatments are contained in the Material Safety Data Sheet (MSDS).

## PROPERTIES

Active Ingredients:	100% of total solids
Specific Gravity:	1.09
pH:	11.5
V.O.C Content:	<50g/L N/A
Flash Point:	N/A
Freeze Point:	0°C
Shelf Life:	1 Year in unopened factory sealed container

## V.O.C.

Less than 50 g/L. Compliant with all US voc regulations including Federal EPA, OTC, LADCO, SCAQMD & CARB.

## PACKAGING

25L Plastic Pail	28kg
50L Mini Drum	58kg
200L Drum	226kg
1000L Tote (IBC)	1150kg



700 Great South Road, Penrose  
P O Box 9826, Auckland, New Zealand  
[www.lesasystems.co.nz](http://www.lesasystems.co.nz)

Tel: 64 9 526 7136 Fax: 64 9 525 2139  
Freephone: 0800 74 LESA (0800 74 5372)  
Email: [sales@lesasystems.co.nz](mailto:sales@lesasystems.co.nz)

# PENTRA-FINISH (HG)



## LIMITATIONS

### FOR PROFESSIONAL USE ONLY

Use on interior surfaces only. Protect from freezing. Agitate before use. Do not allow standing water to dwell on surface for 7 days following application. Do not allow traffic on surface until it is dry-typically 30-60 minutes. **Pentra-Finish™ (HG)** will not bridge or fill cracks, and will not salvage honeycombed or structurally unsound surfaces. **Pentra-Finish™ (HG)** quickly bonds to most surfaces including metal, wood, glass, and paint. Protect adjacent surfaces. Remove overspray quickly with a damp cloth and soap. Always do a test patch before beginning the job to verify coverage, appearance, and surface material variations.

## WARRANTY

**LIMITED WARRANTY NOTICE** Every reasonable effort is made to apply exacting standards both in the manufacture of our products and in the information that we issue concerning these products and their use. We warrant our products to be of good quality and will replace or, at our election, refund the purchase price of any products proved defective. Satisfactory results depend not only upon quality products, but also upon many factors beyond our control. Therefore, except for such replacement or refund.

(CONVERGENT) MAKES NO WARRANTY OR GUARANTEE, EXPRESS OR IMPLIED, INCLUDING WARRANTIES OF FITNESS FOR A PARTICULAR PURPOSE OR MERCHANTABILITY, RESPECTING ITS PRODUCTS, and CONVERGENT shall have no other liability with respect thereto. Any claim regarding product defect must be received in writing within one (1) year from the date of shipment. No claim will be considered without such written notice or after the specified time interval. User shall determine the suitability of the products for the intended use and assume all risks and liability in connection therewith. Any authorized change in the printed recommendations concerning the use of our products must bear the signature of the CONVERGENT's Research Director.

This information and all further technical advice are based on CONVERGENT's present knowledge and experience. However, CONVERGENT assumes no liability for providing such information and advice including the extent to which such information and advice may relate to existing third party intellectual property rights, especially patent rights. In particular, CONVERGENT disclaims all WARRANTIES, WHETHER EXPRESS OR IMPLIED, INCLUDING THE IMPLIED WARRANTIES OF FITNESS FOR A PARTICULAR PURPOSE OR MERCHANTABILITY. CONVERGENT SHALL NOT BE RESPONSIBLE FOR CONSEQUENTIAL, INDIRECT OR INCIDENTAL DAMAGES (INCLUDING LOSS OF PROFITS) OF ANY KIND. CONVERGENT reserves the right to make any changes according to technological progress or further developments. It is the customer's responsibility and obligation to carefully inspect and test any incoming goods. Performance of the product(s) described herein should be verified by testing and carried out only by qualified experts. It is the sole responsibility of the customer to carry out and arrange for any such testing. Reference to trade names used by other companies is neither a recommendation, nor an endorsement of any product and does not imply that similar products could not be used. CONVERGENT reserves the right to change specifications referred to in this literature at any time, without prior notice. The information contained herein is, to our knowledge, true and accurate. While this material is furnished in good faith, no warranty expressed or implied, of merchantability, completeness, fitness or otherwise is made. This material is offered only for your consideration, investigation and verification, and CONVERGENT disclaims any liability incurred from the use thereof and shall not in any event, be liable for any special, incidental or consequential damages arising from such use. This information is not intended to be all inclusive and the manner and conditions of use and handling of any material may involve other or additional considerations specific to the use or user. Nothing herein should be construed as permission or recommendation to infringe any patent or as to any specific use. No agent, representative or employee of this company is authorized to vary any terms of this notice.



700 Great South Road, Penrose  
P O Box 9826, Auckland, New Zealand  
[www.lesasystems.co.nz](http://www.lesasystems.co.nz)

Tel: 64 9 526 7136 Fax: 64 9 525 2139  
Freephone: 0800 74 LESA (0800 74 5372)  
Email: [sales@lesasystems.co.nz](mailto:sales@lesasystems.co.nz)