SKUDO TACK-MAT (LT)







Skudo's Light Traffic (LT) Construction Tack-Mat offers outstanding temporary surface protection that is easy to apply to both vertical and horizontal indoor surfaces, around corners such as stairs and door jams, on countertops, cabinets, windows and more. LT Tack-Mat features a unique self-stick surface. Simply peel the backing paper and apply.

LT Tack-Mat provides interior surface protection for commercial and residential projects for up to 12 months.

PRODUCT DATA

Weight	1m	Mat Thickness	1.6mm	Product SKU	SKUDOTMLT
Length	50m	Roll Weight	23kg		
Surface Area	50m ²	Colour	Gray		

BENEFITS

- Strong bond with the surface blocks any dirt and debris from ever coming into contact with the protected substrate
- Impact protection from carts and foot traffic
- Stain proof protection from small spills of chemicals, solvents, paints, oils etc
- Provides a slip resistant surface that is seamless and stationary
- Can be used in any temperature: -10°C to +50°C
- Easy to adjust or inspect surface, simply peel up and reposition

USES

Protects all edges during construction / remodeling including:

- Most marble, granite, and stone
 Not to be used on bluestone and limestone)
- Hardwood* and laminate
- Ceramic and porcelain tile
- Glass, epoxies, and metals
- Cured concrete
- Vertical surfaces, such as walls, cabinets, doors, framing, and stairs
- Sheet vinyl
- Showers, bathtubs, and countertops (Not acrylic)
- No acrylic surfaces

APPLICATION AND REMOVAL

Skudo LT Tack-Mat is easily applied by eeling off the release paper and pressing down onto the surface. Simply peel up LT Track Mat leaving a clean, undamaged surface. Removal temperature I 0°C-45°C.

*Only use Skudo Tack-Mat on sealed hardwood with a hard wearing factory finished surface (eg: Aluminum Oxide).







700 Great South Road, Penrose P O Box 9826, Auckland, New Zealand www.lesasystems.co.nz Tel: 64 9 526 7136 Fax: 64 9 525 2139 Freephone: 0800 74 LESA (0800 74 5372) Email: sales@lesasystems.co.nz